UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/814,188	04/01/2004	Katsumi Nishijima	8001-1195	6415
466 YOUNG & TH	7590 02/06/200 <b>OMPSON</b>	EXAMINER		
209 Madison Street			WENDELL, ANDREW	
	Suite 500 ALEXANDRIA, VA 22314		ART UNIT	PAPER NUMBER
			2618	
			MAIL DATE	DELIVERY MODE
			02/06/2009	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
	10/814,188	NISHIJIMA ET AL.
Office Action Summary	Examiner	Art Unit
	ANDREW WENDELL	2618
The MAILING DATE of this communication app Period for Reply	pears on the cover sheet with the c	correspondence address
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING D  - Extensions of time may be available under the provisions of 37 CFR 1.1 after SIX (6) MONTHS from the mailing date of this communication.  - If NO period for reply is specified above, the maximum statutory period  - Failure to reply within the set or extended period for reply will, by statute Any reply received by the Office later than three months after the mailin earned patent term adjustment. See 37 CFR 1.704(b).	ATE OF THIS COMMUNICATION (36(a). In no event, however, may a reply be tirwill apply and will expire SIX (6) MONTHS from (6), cause the application to become ABANDONE	N. nely filed the mailing date of this communication. D (35 U.S.C. § 133).
Status		
1) ■ Responsive to communication(s) filed on 19 N     2a) ■ This action is <b>FINAL</b> . 2b) ■ This     3) ■ Since this application is in condition for alloward closed in accordance with the practice under Benefits.	s action is non-final. nce except for formal matters, pro	
Disposition of Claims		
4) ☐ Claim(s) 1-3 and 5-36 is/are pending in the ap 4a) Of the above claim(s) is/are withdra 5) ☐ Claim(s) is/are allowed. 6) ☐ Claim(s) 1-3 and 5-36 is/are rejected. 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/or Application Papers 9) ☐ The specification is objected to by the Examine	wn from consideration. or election requirement.	
10) The drawing(s) filed on is/are: a) accomposed and accomposed accomposed and accomposed accomposed and accomposed accompos	cepted or b) objected to by the drawing(s) be held in abeyance. Set tion is required if the drawing(s) is ob	e 37 CFR 1.85(a). jected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
<ul> <li>12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of:</li> <li>1. Certified copies of the priority document</li> <li>2. Certified copies of the priority document</li> <li>3. Copies of the certified copies of the priority application from the International Burea</li> <li>* See the attached detailed Office action for a list</li> </ul>	ts have been received. ts have been received in Applicati rity documents have been receive u (PCT Rule 17.2(a)).	ion No ed in this National Stage
Attachment(s)  1) Notice of References Cited (PTO-892)  2) Notice of Draftsperson's Patent Drawing Review (PTO-948)  3) Information Disclosure Statement(s) (PTO/SB/08)  Paper No(s)/Mail Date	4) Interview Summary Paper No(s)/Mail D: 5) Notice of Informal F 6) Other:	ate

Art Unit: 2618

#### **DETAILED ACTION**

### Continued Examination Under 37 CFR 1.114

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 11/19/2008 has been entered.

### Claim Rejections - 35 USC § 112

- The following is a quotation of the second paragraph of 35 U.S.C. 112:
   The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.
- 3. Claims1 and 28-29 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

Examiner is unclear about the limitation "for viewing in a direction perpendicular to an upper surface of the lower housing in all positions of the upper housing". Based on Fig. 2A of applicant's drawings it appears the upper housing is perpendicular to the lower housing with the end portion being visible. How applicant claims this is very unclear and it reads as the end portion being perpendicular to the lower housing which can be considered new matter based on Fig. 2A. Examiner recommends cleaning up this language to avoid any new matter situations and better explain what two things are being perpendicular to each other.

Art Unit: 2618

# Claim Rejections - 35 USC § 103

4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

- (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 5. Claims 1-3, 5-7, 18-19, and 24-28 rejected under 35 U.S.C. 103(a) as being unpatentable over Nishimura (US Pat Pub# 2006/0063570) in view of Gauld et al. (US Pat Pub# 2004/0198435) and further in view of Bum (US Pat Pub# 2003/0013417).

Regarding claim 1, Nishimura's portable apparatus teaches a mobile terminal 100 (Fig. 1), comprising a control unit 99 (Fig. 1; Section 0033; obvious there is a control unit to have communication); a display unit 54 and 4 (Fig. 1); an upper housing 51 (Fig. 1); a lower housing 2 (Fig. 1); and a 2-axis hinge unit 3 and 11 (Fig. 3) for coupling the housings 2 and 51 (Fig. 1); wherein an end portion of the 2-axis hinge unit 2 and 51 (Fig. 2) is exposed outside the terminal 1, 4, and 6 (Fig. 2), and an information input device 4 and 6 (Fig. 2) is mounted in the end portion. Nishimura fails to teach a pointing device, a 2-axis hinge unit connected to the lower housing, a control unit, and an end portion being exposed perpendicular to the lower housing in all positions of the upper housing.

Gauld's camera integration on a mobile device teaches a pointing device 17 (Fig. 1) and a control unit 104 (Fig. 4).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a pointing

device as taught by Gauld into Nishimura's portable apparatus in order to provide an intuitive user interface (Sections 0013-0014).

Nishimura and Gauld fail to teach a 2-axis hinge unit connected to the lower housing and an end portion being exposed perpendicular to the lower housing in all positions of the upper housing.

Bum teaches a 2-axis hinge unit 30, 31, 33 (Figs. 1-4) coupling the housings 10 and 20 (Figs. 1-4) for folding and swinging movement of the upper housing relative to the lower housing about intersecting axes (Figs. 1-4, section 0018; can be folded or upper casing can be swing around) both of which are fixed relative to the lower housing 10 (Figs.1-4, hinge unit connected to the lower housing); wherein an end portion of the 2-axis hinge unit 30, 31, 33 (Figs. 1-4) is exposed outside the terminal for viewing in a direction perpendicular to an upper surface of the lower housing 10 (Fig. 4) in all positions of the upper housing 20 (Fig. 4, shows the upper housing being perpendicular which is how the examiner is reading the claims, see 112 rejection for reasoning).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a 2-axis hinge unit connected to the lower housing as taught by Bum into a pointing device as taught by Gauld into Nishimura's portable apparatus in order to make it easier for the user to watch images at the right ratio (Sections 0006-0007).

Regarding claim 2, Gauld further teaches wherein the control unit 104 (Fig. 4) controls the terminal according to an operation of the information input device 16 (Fig. 2).

Regarding claim 3, Gauld further teaches wherein the control unit 104 (Fig. 4) assigns a predetermined function to the information input device (Section 0015).

Regarding claim 5, Gauld further teaches wherein the control unit 104 (Fig. 4) assigns another operating function to the pointing device 17 (Fig. 1 and Sections 0024 and 0044).

Regarding claim 6, Gauld further teaches wherein the information input device 17 (Fig. 1) further comprises a terminal operating function (Section 0024).

Regarding claim 7, Gauld further teaches wherein the terminal operating function is performed by a press (Section 0024). Note, the user has to perform the function, so a press or some pressure has to be performed for a user to have function.

Regarding claim 18, Gauld further teaches wherein the control unit detects an operation of a predetermined operation key to control an operation of the information input device (Section 0015).

Regarding claim 19, Gauld further teaches wherein the control unit controls an operation of the information input device while a predetermined operation key is operated (Section 0015).

Regarding claim 24, Nishimura further teaches wherein the terminal is a mobile telephone 100 (Fig. 1).

Regarding claim 25, Nishimura further teaches wherein the two axes of the 2-axis hinge unit are a folding axis and a horizontal rotation axis (Fig. 3), the upper housing 51 (Fig. 3), the lower housing 2 (Fig. 3) and the 2-axis hinge unit being constructed and arranged so that the end portion of the 2-axis hinge unit on the

horizontal rotation axis is exposed to an outside of the mobile terminal both when the mobile terminal is in an open position and when the mobile terminal is in a closed position (Figs. 2, 5, and 7).

Regarding claim 26, Nishimura further teaches wherein the end portion is exposed on a side face of the lower housing (Fig. 3).

Regarding claim 27, Nishimura further teaches wherein the information device is arranged on the end portion of the 2-axis hinge unit (Figs. 3 and 5).

Regarding claim 28, Nishimura teaches a lower housing 2 (Fig. 3); a 2-axis hinge 11 and 3 (Fig. 3) the connected to the lower housing 2 (Fig. 3); an upper housing 51 (Fig. 3) connected to the 2-axis hinge 3 and 11 (Fig. 3); a display unit 54 (Fig. 3) disposed on the upper housing 51 (Fig. 3); a control unit 99 (Fig. 1; Section 0033; obvious there is a control unit to have communication); and wherein an end portion of the 2-axis hinge unit 3 and 11 (Fig. 3) is exposed outside the terminal 4 (Fig 3) and 6 (Fig. 5), the information input device 4 (Fig 3) and 6 (Fig. 5) is mounted in the end portion. Nishimura fails to teach a button, a 2-axis hinge unit connected to the lower housing, and a control unit.

Gauld teaches a button 16 (Fig. 4) or 17 (Fig. 1) operatively connected to the control unit 104 (Fig. 4) for user input.

Gauld and Nishimura fails to teach a 2-axis hinge unit connected to the lower housing and an end portion being exposed perpendicular to the lower housing in all positions of the upper housing.

Application/Control Number: 10/814,188

Art Unit: 2618

Bum teaches a 2-axis hinge unit 30, 31, 33 (Figs. 1-4) coupling the housings 10 and 20 (Figs. 1-4) for folding and swinging movement of the upper housing relative to the lower housing about intersecting axes (Figs. 1-4, section 0018; can be folded or upper casing can be swing around) both of which are fixed relative to the lower housing 10 (Figs.1-4, hinge unit connected to the lower housing); wherein an end portion of the 2-axis hinge unit 30, 31, 33 (Figs. 1-4) is exposed outside the terminal for viewing in a direction perpendicular to an upper surface of the lower housing 10 (Fig. 4) in all positions of the upper housing 20 (Fig. 4, shows the upper housing being perpendicular which is how the examiner is reading the claims, see 112 rejection for reasoning).

Page 7

6. Claims 8-9 are rejected under 35 U.S.C. 103(a) as being unpatentable over Nishimura (US Pat Pub# 2006/0063570) in view of Gauld et al. (US Pat Pub# 2004/0198435) and further in view of Bum (US Pat Pub# 2003/0013417) and further in view of Schmitt et al. (US Pat# 6,088,585).

Regarding claim 8, Nishimura's portable apparatus in view of Gauld's camera integration on a mobile device and further in view of Bum teaches the limitations in claim 1. Nishimura, Bum, and Gauld fail to teach a fingerprint sensor.

Schmitt's portable telecommunication device including a fingerprint sensor teaches a fingerprint sensor 30 (Fig. 14).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a fingerprint sensor as taught by Schmitt into a 2-axis hinge unit connected to the lower housing as

taught by Bum into a pointing device as taught by Gauld into Nishimura's portable apparatus in order to increase security and reliability (Col. 3 lines 3-11).

Regarding claim 9, the combination including Schmitt teaches wherein the control unit 207 (Fig. 15) can operate the terminal 190 (Fig. 15) when the fingerprint sensor 30 (Fig. 15) detects a predetermined input.

7. Claims 10-16 are rejected under 35 U.S.C. 103(a) as being unpatentable over Nishimura (US Pat Pub# 2006/0063570) in view of Gauld et al. (US Pat Pub# 2004/0198435) and further in view of Bum (US Pat Pub# 2003/0013417) and further in view of Kim (US Pat# 6,621,066).

Regarding claim 10, Nishimura's portable apparatus in view of Gauld's camera integration on a mobile device and further in view of Bumteaches the limitations in claim 1. Nishimura, Bum, and Gauld fail to teach position detection means.

Kim's optimizing opening and closing control of a sub-body in automatic and manual folder type mobile communication terminals teaches position detection means 236, 238, 300 and 302 (Fig. 4) for detecting relative positions between the upper housing and the lower housing

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a sensor detection means as taught by Kim into a 2-axis hinge unit connected to the lower housing as taught by Bum into a pointing device as taught by Gauld into Nishimura's portable apparatus in order to have a more efficient and precise control for opening or closing the sub-body folder upon using of the terminal (Col. 1 lines 51-61).

Regarding claim 11, Kim further teaches wherein the control unit 200 (Fig. 3) controls the terminal based on an output of the position detection means 236 and 238 (Fig. 3).

Regarding claim 12, Gauld further teaches wherein the control unit 104 (Fig. 4) controls an operation of the information input device 16 (Fig. 4).

Regarding claim 13, Kim further teaches wherein the position detection means comprise a magnet 300 and 302 (Fig. 4) and a magnetic sensor 236 and 238 (Fig. 4).

Regarding claim 14, Kim further teaches wherein the magnet 300 and 302 (Fig. 4) and the magnetic sensor 236 and 238 (Fig. 4) are arranged in separate housings (Fig. 4).

Regarding claim 15, Kim further teaches wherein the magnetic sensor is a Hall element (Fig. 4).

Regarding claim 16, Kim further teaches wherein the position detection means detect a turning direction of the housings (Col. 2 line 1-Col. 3 line18).

8. Claim 17 is rejected under 35 U.S.C. 103(a) as being unpatentable over Nishimura (US Pat Pub# 2006/0063570) in view of Gauld et al. (US Pat Pub# 2004/0198435) and further in view of Bum (US Pat Pub# 2003/0013417) and further in view of Kim (US Pat# 6,621,066) and further in view of Ikeda et al. (US Pat# 6,957,083).

Regarding claim 17, Nishimura's portable apparatus in view of Gauld's camera integration on a mobile device and further in view of Bum and further in view of Kim's optimizing opening and closing control of a sub-body in automatic and manual folder type mobile communication terminals teaches the limitations in claims 1, 10, and 16.

Nishimura, Kim, Bum, and Gauld fail to teach a control unit controls the display unit based on the turning direction of the housings.

Ikeda's mobile telephone teaches wherein the control unit controls the display unit based on the turning direction of the housings (Col. 1 line 57-Col. 2 line 44 and Col. 3 line 41-Col. 5 line 60).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a control unit controls the display unit based on the turning direction of the housings as taught by Ikeda into a sensor detection means as taught by Kim into a 2-axis hinge unit connected to the lower housing as taught by Buminto a pointing device as taught by Gauld into Nishimura's portable apparatus in order to make using the camera easier to use (Col. 1 lines 42-56).

9. Claims 20-22 are rejected under 35 U.S.C. 103(a) as being unpatentable over Nishimura (US Pat Pub# 2006/0063570) in view of Gauld et al. (US Pat Pub# 2004/0198435) and further in view of Bum (US Pat Pub# 2003/0013417) and further in view of Wada et al. (US Pat Pub# 2003/0174240).

Regarding claim 20, Nishimura's portable apparatus in view of Gauld's camera integration on a mobile device and further in view of Bum teaches the limitations in claim 1. Nishimura, Bum, and Gauld fail to teach a lock unit.

Wada's mobile telephone teaches a lock unit for locking the 2-axis hinge unit (Section 0055).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a lock unit as taught by Wada into a 2-axis hinge unit connected to the lower housing as taught by Bum into a pointing device as taught by Gauld into Nishimura's portable apparatus in order to increase security (Section 0017 and 0056).

Regarding claim 21, Wada further teaches wherein the lock unit is controlled by an input from the information input device (Section 0055).

Regarding claim 22, Wada further teaches wherein the information input device is a personal authentication sensor (Section 0055); and the lock unit is released when the sensor detects a predetermined input (Section 0055).

10. Claim 23 is rejected under 35 U.S.C. 103(a) as being unpatentable over Nishimura (US Pat Pub# 2006/0063570) in view of Gauld et al. (US Pat Pub# 2004/0198435) and further in view of Bum (US Pat Pub# 2003/0013417) and further in view of Wada et al. (US Pat Pub# 2003/0174240) and further in view of Schmitt et al. (US Pat# 6,088,585).

Regarding claim 23, Nishimura's portable apparatus in view of Gauld's camera integration on a mobile device and further in view of Bum and further in view of Wada's mobile telephone teaches the limitations in claims 1 and 20-22. Nishimura, Gauld, Bum, and Wada fail to teach a fingerprint sensor.

Schmitt's portable telecommunication device including a fingerprint sensor teaches a fingerprint sensor 30 (Fig. 14).

Art Unit: 2618

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a lock unit as taught by Wada into a fingerprint sensor as taught by Schmitt into a 2-axis hinge unit connected to the lower housing as taught by Bum into a pointing device as taught by Gauld into Nishimura's portable apparatus in order to increase security and reliability (Col. 3 lines 3-11).

11. Claims 29-30 are rejected under 35 U.S.C. 103(a) as being unpatentable over Nishimura (US Pat Pub# 2006/0063570) in view of Bum (US Pat Pub# 2003/0013417). Regarding claim 29, Nishimura teaches a two-axis hinge 3 and 11 (Fig. 3) having a horizontal rotating axis and a folding axis for coupling the upper housing 51 (Fig. 3) and the lower housing 2 (Fig. 3), and adapting the housings for foldable rotation around the folding axis or an open-close operation (Figs. 3 and 5-6) and for horizontal rotation around the horizontal rotation axis (Figs. 3 and 7-9); and an information input device 4 (Fig. 3) and 6 (Fig. 5) arranged on top of one end portion or the horizontal rotation axis 3 and 11 (Fig. 3), the input device 4 (Fig. 3) and 6 (Fig. 5) being exposed to an outside of the mobile terminal both when the mobile terminal is in a closed position and when the mobile terminal is in an open position (Figs. 3, 5-6, 21-22, and 23-24). Nishimura fails to teach a two-axis hinge both being fixed relative to the lower housing and an end portion being exposed perpendicular to the lower housing in all positions of the upper housing.

Bum teaches a 2-axis hinge unit 30, 31, 33 (Figs. 1-4) having a horizontal rotation axis and a folding axis (Figs. 1-4, section 0018; can be folded or upper casing

can be swing around) for coupling the upper housing 20 (Figs. 1-4) and the lower housing 10 (Figs. 1-4), and adapting the housing for foldable rotation around the folding axis for an open-close operation and for horizontal rotation around the horizontal rotation axis (Figs. 1-4, section 0018; can be folded or upper casing can be swing around), both of which are fixed relative to the lower housing 10 (Figs.1-4, hinge unit connected to the lower housing); wherein an end portion of the 2-axis hinge unit 30, 31, 33 (Figs. 1-4) is exposed outside the terminal for viewing in a direction perpendicular to an upper surface of the lower housing 10 (Fig. 4) in all positions of the upper housing 20 (Fig. 4, shows the upper housing being perpendicular which is how the examiner is reading the claims, see 112 rejection for reasoning).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a two-axis hinge both being fixed relative to the lower housing as taught by Bum into Nishimura's portable apparatus in order to improve adaptability of user interfaces and reducing manufacturing time and costs (Col. 2 lines 13-16).

Regarding claim 30, the combination including Nishimura teaches wherein the horizontal rotation axis 11 (Fig. 3) is mounted on the lower housing 2 (Fig. 3) with another end portion making a right angle with a surface of the housings 2 and 51 (Fig. 3); and the folding axis 3 (Fig. 3) is mounted in the upper housing 51 (Fig. 3), and is joined together with the horizontal rotation axis 11 (Fig. 3) by crossing through the horizontal rotation axis at a right angle for providing the foldable rotation and the horizontal rotation to the upper housing (Figs. 1-3).

12. Claims 31 and 34-35 are rejected under 35 U.S.C. 103(a) as being unpatentable over Nishimura (US Pat Pub# 2006/0063570) in view of Bum (US Pat Pub# 2003/0013417) and further in view of Kim (US Pat# 6,621,066).

Regarding claim 31, Nishimura in view of Bum teaches the limitations in claims 29-30. Nishimura and Bum fails to teach a detection unit.

Kim teaches a position detection unit 236, 238, 300 and 302 (Fig. 4) for detecting one of relative positions between the upper housing 120 (Fig. 1A) and the lower housing 110 (Fig. 1A), wherein the relative positions include a first position in which the upper housing is closed and overlaid on the lower housing and wherein the display unit and the operation key unit are facing each other, a second position in which the upper housing is opened from the first position by the foldable rotation, a third position in which the upper housing is turned 180 degrees from the first position by the horizontal rotation, a fourth position in which the upper housing is turned 90 degrees from the second position by the horizontal rotation, and fifth position in which the upper housing is further turned 90 degrees from the fourth position by the horizontal rotation (Figs. 3-4).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a sensor detection means as taught by Kim into a two-axis hinge both being fixed relative to the lower housing as taught by Bum into Nishimura's portable apparatus in order to have a more efficient and precise control for opening or closing the sub-body folder upon using of the terminal (Col. 1 lines 51-61).

Regarding claim 34, Kim further teaches wherein the position detection unit comprises a magnet 300 and 302 (Fig. 4) and a magnet sensor 236 and 238 (Fig. 4) each arranged in a different the housing from each other (Fig. 4).

Regarding claim 35, Kim further teaches wherein the magnet sensor is a Hall element (Fig. 4).

13. Claim 32 is rejected under 35 U.S.C. 103(a) as being unpatentable over Nishimura (US Pat Pub# 2006/0063570) in view of Bum (US Pat Pub# 2003/0013417) and further in view of Kim (US Pat# 6,621,066) and further in view of Gauld et al. (US Pat Pub# 2004/0198435).

Regarding claim 32, Nishimura in view of Bum and further in view of Kim teaches the limitations in claims 29-31. Nishimura, Bum, and Kim fail to teach a pointing device.

Gauld teaches wherein the information input device is a pointing device 17 (Fig. 1) for selecting a pointer shown on the display unit 14 (Fig. 1), and the mobile terminal further comprising a control unit 104 (Fig. 4) to control an operation of the pointing device so as to disable the operation of the pointing device.

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a pointing device as taught by Gauld into a sensor detection means as taught by Kim into a two-axis hinge both being fixed relative to the lower housing as taught by Bum into Nishimura's portable apparatus in order to provide an intuitive user interface (Sections 0013-0014).

14. Claim 33 is rejected under 35 U.S.C. 103(a) as being unpatentable over Nishimura (US Pat Pub# 2006/0063570) in view of Bum (US Pat Pub# 2003/0013417) and further in view of Kim (US Pat# 6,621,066) and further in view of Gauld et al. (US Pat Pub# 2004/0198435) and further in view of Ikeda et al. (US Pat# 6,957,083).

Regarding claim 33, Nishimura in view of Bum and further in view of Kim and further in view of Gauld teaches the limitations in claims 29-32. Nishimura, Gauld, Bum, and Kim fail to teach a control unit controls the display unit based on the turning direction of the housings.

Ikeda teaches wherein the control unit controls a display operation based on the pointing device so as to select the pointer on the display unit of an opposite direction of right and left when the third position is detected by the position detection unit (Col. 1 line 57-Col. 2 line 44 and Col. 3 line 41-Col. 5 line 60).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a control unit controls the display unit based on the turning direction of the housings as taught by Ikeda into a pointing device as taught by Gauld into a sensor detection means as taught by Kim into a two-axis hinge both being fixed relative to the lower housing as taught by Bum into Nishimura's portable apparatus in order to make using the camera easier to use (Col. 1 lines 42-56).

15. Claim 36 is rejected under 35 U.S.C. 103(a) as being unpatentable over Nishimura (US Pat Pub# 2006/0063570) in view of Bum (US Pat Pub# 2003/0013417) and further in view of Schmitt et al. (US Pat# 6,088,585).

Art Unit: 2618

Regarding claim 36, Nishimura in view of Bum teaches the limitations in claim 29.

Nishimura and Bum fail to teach a fingerprint sensor.

Schmitt teaches a fingerprint sensor 30 (Fig. 14).

Therefore, it would have been obvious at the time of the invention to one of ordinary skill in the art at the time the invention was made to incorporate a fingerprint sensor as taught by Schmitt into a two-axis hinge both being fixed relative to the lower housing as taught by Bum into Nishimura's portable apparatus in order to increase security and reliability (Col. 3 lines 3-11).

# Response to Arguments

16. Applicant's arguments with respect to claim1-3 and 5-36 have been considered but are most in view of the new ground(s) of rejection.

#### Conclusion

Any inquiry concerning this communication or earlier communications from the examiner should be directed to ANDREW WENDELL whose telephone number is (571)272-0557. The examiner can normally be reached on 7:30-5 M-F.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Nay Maung can be reached on 571-272-7882. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2618

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Andrew Wendell/ Examiner, Art Unit 2618 /Nay A. Maung/ Supervisory Patent Examiner, Art Unit 2618

1/30/2009